Product Guide Sheet Stablemate II Access Platforms

Our best selling Stablemate Access Platforms offer the ideal solution to you needs, when elevation is needed during stocktaking, inspection etc.

To fit; simply drive the truck slowly into the platform sleeves, once the forks are fully sleeved simply re-fit the heel pin behind the truck forks, thus retaining the attachment.

Note: The truck parking brake must be applied when personnel are inside the platform. Vertical movement permitted only.

All Platforms comply to PM28.



Stablemate Platforms are the perfect answer for stocktaking, high level maintenance or routine inspection. A superior platform manufactured to a high specification. All have safety harness rails and positive heel locking. Where gates are fitted, locks operate automatically when the platform is raised.

Model Ref.	Access	А	В	С	D	E
WP-SP	Lift Up Bar	800mm	800mm	794mm	1860mm	1070mm
WP-STD	Through Bars	1220mm	1000mm	794mm	1860mm	1070mm
WP-SPG	Front Gate	1000mm	1000mm	794mm	1860mm	1070mm
WP-GATED	Side Gate	1220mm	1000mm	794mm	1860mm	1070mm
WP-ULTIMATE	Side Gate	1220mm	1000mm	794mm	1860mm	1070mm

Model Ref.	Weight	C of G	No. Of People	Capacity
WP-SP	74kgs	300mm	1	300kgs
WP-STD	108kgs	500mm	2	500kgs
WP-SPG	99kgs	427mm	1	300kgs
WP-GATED	114kgs	496mm	2	500kgs
WP-ULTIMATE	148kgs	469mm	2	500kgs

Ordering Information

Fork Width & Thickness? Fork Spread? Truck Capacity? Type Of Operation? No. of Personnel to be carried?

Optional Extras

C – Standard Castors T – Tool Tray SH – Safety Harness and Lanyard OG – Overhead Guard SLB – Strip Light Bulb Holder

