



Hand stacker model HG

Capacity 300 and 500 kg

Ideal for the occasional, internal application of stacking and transporting of palletised goods.

Features

- Manual winch for exact positioning of the height.
- Handlebar for easy operation.
- C-profile mast with maintenance free pulley and guide rollers with ball bearings.
- Steering roller with brake for safe parking of the hand stacker.

Technical data model HG

Model	HG 0315	HG 0515
Art.-No.	034518016	034518017
Capacity, kg	300	500
Load center c, mm	400	600
Wheelbase y, mm	850	1050
Weight, kg	80	90
Tyre type*	PA/PA	PA/PA
Steering rollers, mm	125x40	125x40
Load rollers, mm	75x30	75x30
Number of wheels/load rollers	2/2	2/2
Height, mast retracted h1, mm	1840	1840
Free lift h2, mm	1410	1410
Stroke h3, mm	1410	1410
Height, mast extended h4, mm	1840	1840
Lifting height max. h3+h13, mm	1500	1500
Fork height lowered h13, mm	90	90
Overall length L1, mm	1020	1320
Length incl. apron L2, mm	362	362
Overall width B, mm	710	710
Fork height s, mm	50	50
Fork width e, mm	160	160
Fork length l, mm	600	900
Outside dimension of forks b1, mm	580	580
Ground clearance m1, mm	30	30
Turning circle radius Wa, mm	855	1155
Lift per one crank rotation with/without load, mm	25	25

*PA... Polyamide

