

**EXOFIT™ XP FULL BODY HARNESS
WITH PERSONAL FLOTATION DEVICE (PFD)**



**Fall Arrest
And Buoyancy
Protection.
Designed For use
in Open Or Closed
Waters.**

- Automatic and manual operation of PFD(Personal Flotation Device).
- Stainless steel hardware for enhanced corrosion resistance in harsh environments.
- Front loops for fall arrest and Large rear D-ring for connections to fall protection systems.



EQUIPPED

EXOFIT™ XP FULL BODY HARNESS WITH PERSONAL FLOTATION DEVICE (PFD)



NOTE: After gas inflation, the PFD must be returned to a service agent to be re-armed.

How the Personal Flotation Device (PFD) works.

It will activate and begin to inflate once it has been immersed in the water for three seconds. The inflation technology is based on water pressure, eliminating activation due to unintentional or accidental contact with water, such as rain or spray. The device can also be operated manually; simply pull the toggle. There is an inflation tube for oral inflation, which can also be used to deflate the life jacket.

Buoyancy Protection is measured in Newtons (N).

Our integrated PFD's have 275 Newtons of buoyancy to provide additional support and safety in the water, as well as exceptional turning capacity to self right the wearer. The units buoyancy makes it ideal for use in conjunction with industrial clothing and equipment.



Reflexite® reflective patches, ensures high visibility for rescue and recovery after inflation



Whistle, helps attract attention in rescue and recovery situations



Oral inflation/deflation tube, allows the user to top up with air if required and deflate the PFD after use.



Built-in Lifting becket, for quick and easy rescue and recovery from the water

EXOFIT™ XP FLOTATION HARNESS MODEL:

Flotation Harness with 275N PFD for Open or Closed Waters:

1102169: Medium **1102170:** Large **1102171:** Extra Large

This life jacket is single chambered with automatic gas inflation.



Specifications:

Harness - Webbing: 100% Polyester, width - 45mm, minimum breaking load >26kN **Thread:** 100% Polyester

Hardware: Rear D-ring stainless steel, minimum break strength >22kN, Pass through buckles - legs & Chest, stainless steel, Shoulder adjusters - Spring loaded, stainless steel. **ExoFit™ XP Back & Leg Pad:** Hydrofil® nylon and 3-D mesh lining.

Weight (approx): 2.7kg (with 275N PFD) **Capacity:** 136kg **Standards:** CE EN361, ANSI OSHA.

PFD - Dimensions (packed): 275N - H - 40cm, W - 30cm, D - 4cm **Outer Cover:** Fabric - Heavy Duty Polyurethane coated Nylon, Colour - Red. **Inflatable chamber:** Fabric - 210 Denier Nylon with a weldable Polyurethane Coating, Colour - International orange, Visibility - MED/SOLAS Retro reflective patches. **Closure:** Black Delrin zipper with double quick release openings **Whistle:** Marine Grade - orange in colour. SOLAS / MED Approved **Flotation:** 305N (total inflated buoyancy)

Inflation System: Via mouth inflation/deflation tube or united moulders automatic inflator with manual override.

Capacity: For all persons 40kg - 150kg **Standards:** 275N model - ISO 12402-1 & EN399-1993.

©2010, Capital Safety

Capital Safety Group (Europe, Middle East, Africa)

Le Broc Center - Z.I. 1^{re} Avenue 5600 m - BP 15 - 06511 Carros Le Broc Cedex - France

Tel: +33 (0)4 97 10 00 10 • Fax : +33 (0)4 93 08 79 70

information@capitalsafety.com - www.capitalsafety.com

Capital Safety Group Northern Europe Ltd

7, Christleton Court, Manor Park - Runcorn - Cheshire - WA7 1ST - UK

Tel: +44 (0) 1928 571324 • Fax: +44 (0) 1928 571325

csgne@capitalsafety.com - www.capitalsafety.com