

# Fork Mounted Articulating Extending Jib (FMXA)

*Our Fork Mounted Extending Jib offers the flexibility to handle varying loads at different load centres. The manually extendable inner beam can be moved to suit your desired load centre and offer a solution to previously inaccessible loads. To fit, simply drive slowly forwards into the attachment, until the truck forks are fully sleeved, then simply fit the heel pins provided behind the forks to retain the attachment. Ensure the attachment is fully secured before lifting commences.*

CONTACT Fork Mounted Articulating Extending Jibs are designed to handle loads at variable heights, this extending jib comes complete with two hooks and can be adjusted to 45 degrees at 15 degree increments.

Model Ref	Truck Capacity (kg)	Max Fork Size (mm)	Fork Spread (mm)	Weight (kg)	C of G (Min) (kg)	C of G (Max) (kg)
FMXA-500-2.2	2500	125 X 50	496	282	710	790
FMXA-500-2.7	3000	150 X 50	546	330	800	880
FMXA-500-3.1	3500	150 X 50	546	332	800	880
FMXA-500-3.5	4000	150 X 50	546	332	800	880

**Ordering Information**  
 Truck Capacity  
 Fork Width/Thickness/Spread  
 Load Details



Model Ref.	Capacity (kgs) @ Load Ctrs (mm)								
	1000	1250	1500	1750	2000	2250	2500	2750	3000
500-1.8	1100	900	720	580	500	360	330	260	210
500-2.2	1400	1100	1000	850	750	560	440	320	230
500-2.7	1450	1200	1100	900	840	670	490	360	270
500-3.1	1900	1500	1200	1000	900	730	580	450	370
500-3.5	2000	1600	1300	1100	1000	820	670	540	460
500-4.4	2700	2200	1850	1400	1100	900	750	620	500