


# Hoisting Equipment Electric chain hoists


## Technical data model CPE/CPEF

Model	EAN-No. 4025092*	Capacity in kg/ number of chain falls	Chain dimensions d x p mm	FEM classification	Lifting speed main lift m/min	Lifting speed fine lift m/min	Hoist motor kW	Motor rating ED %
CPE 16-8	*073240	1600/1	11 x 31	1 Am	8	-	2.3	40
CPEF 16-8	*073257	1600/1	11 x 31	1 Am	8	2	2.3/0.58	40/20
CPE 20-8	*073264	2000/1	11 x 31	1 Bm	8	-	2.8	25
CPEF 20-8	*073271	2000/1	11 x 31	1 Bm	8	2	2.8/0.7	25/15
CPE 25-5	*073288	2500/1	11 x 31	1 Am	5	-	2.3	40
CPEF 25-5	*073295	2500/1	11 x 31	1 Am	5	1.25	2.3/0.58	40/20
CPE 30-5	*073301	3000/1	11 x 31	1 Bm	5	-	2.8	25
CPEF 30-5	*073318	3000/1	11 x 31	1 Bm	5	1.25	2.8/0.7	25/15
CPE 32-4	*073325	3200/2	11 x 31	1 Am	4	-	2.3	40
CPEF 32-4	*073332	3200/2	11 x 31	1 Am	4	1	2.3/0.58	40/20
CPE 40-4	*073349	4000/2	11 x 31	1 Bm	4	-	2.8	25
CPEF 40-4	*073356	4000/2	11 x 31	1 Bm	4	1	2.8/0.7	25/15
CPE 50-2	*073363	5000/2	11 x 31	1 Am	2.5	-	2.3	40
CPEF 50-2	*073370	5000/2	11 x 31	1 Am	2.5	0.6	2.3/0.58	40/20
CPE 75-1.6	*079907	7500/3	11 x 31	1 Am	1.6	-	2.8	40
CPEF 75-1.6	*079914	7500/3	11 x 31	1 Am	1.6	0.4	2.8/0.58	40/20
CPE 100-2	*060585	10000/4	11 x 31	1 Am	2.5	-	2 x 2.3	40
CPEF 100-2	*060592	10000/4	11 x 31	1 Am	2.5	0.6	2 x 2.3/0.58	40/20

Model	Net weight* suspension hook kg	Net weight* push trolley kg	Net weight* geared trolley kg	Net weight* electric trolley** kg
CPE 16-8	88	150	154	164
CPEF 16-8	93	155	159	169
CPE 20-8	88	150	154	164
CPEF 20-8	93	155	159	169
CPE 25-5	88	150	154	164
CPEF 25-5	93	155	159	169
CPE 30-5	88	150	154	164
CPEF 30-5	93	155	159	169
CPE 32-4	107	169	173	182
CPEF 32-4	112	174	178	187
CPE 40-4	107	169	173	182
CPEF 40-4	112	174	178	187
CPE 50-2	107	169	173	182
CPEF 50-2	112	174	178	187
CPE 75-1.6	-	-	-	-
CPEF 75-1.6	-	-	-	-
CPE 100-2	282	-	385	406
CPEF 100-2	287	-	390	411



**Festooned cable systems**  
see page 104-105



\*Weight for standard 3 m lift. Other lifting heights on request.

\*\*Additional weight for 2 speed version 2.0 kg.

\*\*\*Limit switches for highest and lowest hook positions - 42 V low voltage control.

## Technical data trolleys

Capacity kg	Size	Beam flange width mm	Beam flange thickness t max. mm	Curve radius min. m	Electric trolley travel speed m/min at 50 Hz	Electric trolley motor kW at 50 Hz
1600 - 5000	A	98 - 180	27	2.0	11 or 11/2.8	0.37 or 0.3/0.09
1600 - 5000	B	180 - 300	27	1.8	11 or 11/2.8	0.37 or 0.3/0.09
7500 - 10000	B	125 - 310	40	1.8	5 or 5/1.25	0.55 or 0.55/0.12