



THE EXOFIT™ XP : ALL DAY COMFORT IN A HARNESS YOU CAN TRUST.

The ExoFit™ XP is the most comfortable, user-friendly harness on the market today!

- The industry's first "truly washable" harness with removable padding.
- State-of-the-art 3-D mesh wicks moisture keeping you cool and delivering all-day comfort.
- Unique spring loaded "stand-up" dorsal D-ring* with visual fall indicator ensures fast, easy and safe connections.
- Superior "X" design padding wraps around the wearer for the ultimate in no-tangle donning.
- Color coded quick-connect buckles make it easy to put on and fit the harness every time.
- Meets or exceeds all applicable industry standards including OSHA, ANSI, the stringent ANSI Z359.1 and CE EN361 and CE358.



Ultimate Comfort The ExoFit XP incorporates new material technology to deliver the ultimate in comfort. State-of-the-art 3-D mesh lining allows moisture to evaporate and cool air to circulate throughout the shoulder, back, hip and leg pads. This padding is removable as well as completely washable - another industry first. The cushioned leg and hip straps offer comfort and additional security during a fall. The "soft" edging prevents chafing and the lightweight webbing is strong without feeling stiff and coarse.

Ease-of-Use ExoFit XP's superior "X" design wraps around the wearer for the ultimate in no-tangle donning and comfortable security. The spring loaded "stand-up" dorsal D-ring ensures an easy connection to a lanyard or SRL without straining to reach it. The harness incorporates a multi-point adjustment system and an adjustable dorsal D-ring for a perfect fit every time. The XP's industry-first quick-connect buckles are now color coded (silver leg buckles and black chest and waist buckles) making donning as easy as 1-2-3. The "easy-grip" end tabs provide something to hold onto when adjusting the straps.

Total Safety Another industry-first is the built-in impact indicator on the dorsal D-ring. Integrated lanyard keepers serve two functions : they provide a connection point for your lanyard when not in use, and for added safety it will snap-free upon "snagging" eliminating trip-fall hazards. Web strap keepers also prevent dangerous entanglements. A properly positioned pelvic strap distributes forces during a fall.

Specifications :

- **Webbing** - 45mm width, 100% Polyester, Minimum Breaking Strength >2600 daN
- **Quick Connect buckles** - Minimum Breaking Strength >1700 daN, Heat treated alloy steel, zinc plating with black e-coat finish on waist, chest, clear chromate finish on legs.



ExoFit™ XP CE Harness Models

2 point front + rear attachment points

- Small** - KB11109745
- Medium** - KB11109746
- Large** - KB11109747

2 point front + rear attachment points with work positioning belt (shown above)

- Small** - KB11100585
- Medium** - KB11100586
- Large** - KB11100587

- **Thread** - High strength, 100% Polyester
- **D-rings** - Minimum Breaking Strength >2200 daN, Heat treated forged alloy steel, clear chromate zinc plating finish
- Meets or exceeds all applicable industry standards including OSHA, the stringent ANSI Z359.1, and CE EN361 and EN358.

Capital Safety

Europe, Middle East, Africa : +33 (0) 497 10 00 10 • Northern Europe : +44 (0) 1928 57 1324
 USA : 800.328.6146 • Canada : 800.387.7484 • Asia : + 852 2992 0381 • Australia/New Zealand : 800 245 002
www.capitalsafety.com • info@capitalsafety.com

