

ULTRA-LOK® RSQ SELF-RETRACTING LIFELINE WITH RESCUE



World's First Dual-Mode Self-Retracting Lifeline Fall Arrest and Rescue

- Exclusive design provides both fall arrest with assisted rescue capabilities and automatic self rescue for ultimate versatility.
- Fall arrest mode stops falls within few decimetres and limits the forces to 6kN or less for added safety.
- Assisted rescue procedures can then be implemented either at the mode selector or remotely with a First-Man-Up™ pole.
- Self rescue mode automatically lowers the user to the next level after a fall.
- Lightweight and long lasting durable reinforced plastic housing. Incorporates a built-in carrying handle for easy transportation.
- 15 m cable extends and retracts automatically enabling the user to move around the work area protected.
- i-Safe™ Intelligent Safety System is built-into every unit to track inspections, control inventory and manage information.
- Designed to meet worldwide standards including CE EN360 and EN341.

i
SAFE[™]
INTELLIGENT
SAFETY SYSTEM
EQUIPPED

ULTRA-LOK® RSQ SELF-RETRACTING LIFELINE WITH RESCUE



Fall Arrest Mode Assisted Rescue

After setting the fall arrest mode, should a fall occur, the following will happen :

A speed sensing brake stops the fall, reduces forces imposed on the user to safe levels of 6kN or less and allows for assisted rescue to take place.



Fall Arrest Mode Assisted Rescue by Hand



Fall Arrest Mode Assisted Rescue by Pole



Accessories for assisted rescue with 4.8m pole

3500100
Assisted Rescue Tool Only



3500102
First-Man-Up™ Pole with Assisted Rescue Tool

These Assisted Rescue Options "engage" the Automatic Rescue Mode.
Traditional assisted rescue operations may also be conducted.

Automatic Rescue Mode Self Rescue Descent

After setting the automatic rescue mode, the device will operate like a descender, should a fall occur, the following will happen :

A speed sensing brake slows the fall, then instantly a centrifugal brake activates, lowering the user at a controlled speed to the next level or ground.



Automatic Rescue Mode Self Rescue/Descent



Ultra-Lok® RSQ Models - Self-Retracting Lifeline with rescue

- 3504553:** 15m length, galvanised cable
- 3504554:** 15m length, stainless steel cable
- 3504555:** 15m length, stainless steel cable and hook

- Accessories:** **3500100:** Assisted Rescue Tool
3500102: First-Man-Up™ Pole with Assisted Rescue Tool

Specifications:

Rated capacity: 34kg to 141kg **Maximum arresting force:** 6 kN **Descent Speed:** 1 m/s **Length of cable:** 15m **Size:** 20cm wide 29cm long, 9cm thick **Weight:** 8.5kg **Housing Material:** 2 pieces, thermoplastic composite **Cable material:** 5mm, 7x19 galvanised cable **Snap Hook:** Zinc plated alloy steel, self locking and swiveling, 22.2kN tensile strength **Standards:** Meets CE EN 360 and EN341.

Capital Safety Group EMEA
Le Broc Center - Z.I. 1^{re} Avenue - BP15
06511 Carros le Broc Cedex - France
Tél : +33 (0) 4 97 10 00 10 - Fax : +33 (0) 4 93 08 79 70
www.capitalsafety.com • information@capitalsafety.com

Capital Safety Northern Europe Ltd
7, Christleton Court - Stuart Road
Manor Park - Runcorn - Cheshire - WA7 ST - UK
Tel : +44 (0) 1928 571324 - Fax : +44 (0) 1928 571325
www.capitalsafety.com • csgne@capitalsafety.com

Ref.: A01RSQTDEN Ind.0