



Twin-Leg 100% Tie-Off Design Provides Continuous Fall Protection and Added Mobility.

- **The industry's first twin-leg SRL is truly unique and innovative**
- **Quick-connect handle and built-in strap secures SRL directly to the harness and keeps unit in position**
- **Two separate 1.8m lifelines extend and retract as the worker moves, providing continuous fall protection without restrictions**
- **Impact indicator on each lifeline makes inspections quick and easy**
- **Compact, lightweight design does not hinder movement providing increased worker comfort and productivity**
- **Durable nylon plastic housing features a non-obtrusive design with rounded corners, providing all-day comfort**
- **Meets EN 360 CE standards**

TALON™ 100% TIE-OFF SELF RETRACTING LIFELINE KD1TALTWIN



Continuous Protection. The 100% Tie-Off Talon with twin-legs provides continuous fall protection and a significant increase in mobility. The unique design allows the user to attach one lifeline leg to the anchor point, move to a new location and connect the second, then disconnect the first and move again. This "leap-frog" action provides 100% protection while moving from one location to another. Each lifeline works independently, extending up to 1.8m and automatically retracting providing fall protection and mobility 100% of the time!

Reduced Fall Distances and Forces. Talon's automatic, inertia activated brake will lock quickly stopping a falling worker within inches - providing more protection at low heights. With the lifeline secured overhead, the total fall distance

(free-fall + deceleration) is limited to 1m or less. By reducing the fall distance, the arresting forces are also minimised, therefore decreasing the impact on the worker.

User Friendly Talon quickly and easily attaches directly to the back of the user's harness by means of the built-in quick-connect handle. A securing strap holds the Talon in the correct position, preventing it from moving around during the users work activities.

The twin-leg lifeline hooks can simply be attached to the front of the harness when not in use, keeping them out of the way. The small and lightweight housing comfortably stays on the user's back, out of the way, but always ready to stop the fall.



< **KD1TALTWIN**
Shown Each Talon
Includes Delta™
Comfort Pad
and Two Lanyard
Keepers

Harness >
Attachment
Detail



Talon 100% Tie-Off Model:

KD1TALTWIN with 2007153 60 mm throat opening aluminum hook on each lifeline, includes Delta™ Comfort Back Pad (9501207) and two Lanyard Keepers (9504374)

Specifications:

Lifeline: 1.8m length each leg, 25mm wide nylon lifeline **Housing:** Nylon plastic **Hook:** 5,000 lb. minimum tensile strength, 2007153 = 60 mm gate opening, aluminum **Capacity:** 100kg. **Anchorage Handle:** Steel, locking type, quick-connect **Retraction Spring:** Stainless steel **Brake:** Heat treated alloy steel and stainless steel **Size:** 18cm length x 10cm width x 7cm thick **Weight:** 2.6kg **Max. Arresting Force:** 600daN. **Maximum Arresting Distance:** 1m **Average Locking Speed:** 1.3m/s **Standards:** Meets or exceeds all applicable industry standards including OSHA, ANSI Z359.1, CSA Z259.2.2 CE EN360.

Capital Safety

USA : 800.328.6146 • Canada : 800.387.7484 • Asia : + 65-6558 7758 • Australia 1800 245 002 • New Zealand : 0800 212 505
Europe, Middle East, Africa : +33 (0) 497 10 00 10 • Northern Europe : +44 (0) 1928 571324
www.capitalsafety.com • information@capitalsafety.com • csgne@csgne.co.uk

Ref : A01TALONTLTDEN Ind. 1