



Compact, Lightweight and Extremely Durable Self Retracting Lifeline for Demanding Worksites

- 4.5m of cable lifeline delivers the greatest working range for economy class self-retracting lifelines
- Lightweight and compact design weighs only 2.9kg
- Rugged aluminum and steel construction provides added durability
- Swiveling anchorage helps keep the unit in line with the anchorage and prevents twisting of cable
- Kevlar®/Nomex® covered external shock pack reduces the forces imposed on the user and also acts as an impact indicator for visual inspection
- Meets all applicable industry standards including CE EN360



4.5m Lifeline

The Rebel™ contains 4.5m of galvanized cable lifeline which maximizes freedom of movement. The 4.5m length enhances worker productivity by adding 2.5m of movement compared to a standard 2m lanyard.

Compact and Lightweight

The Rebel™ delivers one of the industry's best length to weight ratios. The rugged aluminum housing and steel working components can withstand the toughest jobs. Weighing only 2.9kg, the compact design (14cm diameter x 5cm deep) incorporates a smooth housing with rounded corners for added comfort and ease-of-use for added worker productivity and reduced worker fatigue.

Maximum Durability

The Rebel™ is for use in harsh environments where web lifelines just won't cut it. The cable lifeline offers added protection against heat and wear. It can be used for applications and markets involving hot work such as metal cutting, welding, and applications with sharp abrasive objects that require added durability.

Arresting Capabilities

The Rebel™ incorporates a unique speed sensing brake that keeps forces to a minimum and reduces clearance requirements. With a maximum arresting force of 6kN, it supports a capacity of 140kg.

Standards, Warranty & Recertification

Reliability that saves you worry, time and money. The product complies with CE, OSHA and ANSI requirements.

Capital Safety

USA: 800.328.6146
Canada: 800.387.7484
Asia: +65 6558 7758
Australia: 1800 245 002
New Zealand: 0800 212 505
Europe, Middle East, Africa: +33 (0)4 97 10 00 10
Northern Europe: +44 (0) 1928 571324

MODEL AD115



Rebel™ Models

AD115: Rebel™ self retracting lifeline, 4.5m galv. cable lifeline.

Specifications:

Lifeline: 4.5m of 5mm galvanized cable, 7x19 construction

Shock Pack Cover : 60% Kevlar®, 40% Nomex®

Housing: Anodized aluminum.

Snap Hook: Zinc plated alloy steel, 22.2 kN minimum tensile strength with 16kN rated gate.

Capacity: 140 kg.

Retraction spring: Stainless Steel

Size: 13.75 cm in diameter x 5 cm thick.

Weight: 2.9 kg.

Maximum Arresting Force: 6kN.

Maximum Arresting Distance: 2m

Average lock up speed: 1.35m/sec.

Standards: Meets applicable CE EN360, OSHA 1926.502, OSHA 1910.66, ANSI Z359.1 and ANSI A10.32.

Rebel™