



Hydraulic spreader model YHS

Max. capacity 0.5 - 1.5 t

These universal power tools can be used for all repair, maintenance and assembly work requiring precisely controlled power, e.g. aligning of containers and shells, lifting, positioning or aligning of machinery and structural components, forcing-off of shutterings and moulds. Applications are unlimited ...

The spreaders can be operated with all hand pumps.

Features

- Operating pressure max. 700 bar.
- Single-acting with spring return.
- Works in all positions.
- Spreader arms from high tensile steel.
- Incl. female coupler half CFY-1 with dust cap.

Technical data model YHS

Model	EAN-No. 4025092*	Capacity max. kN	Capacity max. t	Max. operating pressure bar	Oil volume max. cm ³	Spread width min. mm	Spread width max. mm	Weight kg
YHS-05	*157650	5	0.5	700	10	16	100	1.9
YHS-11	*154741	10	1.0	700	10	14	100	2.1
YHS-15	*154673	15	1.5	700	70	35	220	6.9



Hydraulic chain cutter model YCC-1.2

This hydraulic chain cutter has been designed for cutting high tensile, grade 8 chains up to a material diameter of 13 mm. The open design allows easy positioning of the chain. The unit can be operated using the standard hand or motor pumps, e.g. mini hydraulic pumps: Model PAY-6, electric power packs: Model PY-04/2/5/2 M, hand pump: Model HPS-2/0.7A.

Features

- Operating pressure max. 700 bar.
- Max. cutting force: 23 t.
- Cutting performance: 13 mm Ø (chain grade 8).
- Max. opening of blades: 30 mm.
- Dimensions (L x W x H): 310 x 140 x 180 mm.
- Weight: 17 kg.
- Built-in standard hydraulic cylinder.
- Single-acting with spring return.
- Durable, heat treated cutting blades easy replacement, blades can be re-sharpened.
- Also useable for cutting full material.
- Highly secured working through protection guard.
- Ready to use, includ. coupler-half, female.