

## Technical data model HF/SM

Model	HF 015-078 SM	HF 030-084 SM	HF 050-090 SM	HF 080-105 SM	HF 100-105 SM	HF 125-105 SM
Art.-No.	24501078	24503084	24505090	24508105	24510105	24512105
Capacity, kg	150	300	500	800	1000	1250
Platform height max. h <sub>2</sub> , mm	780	840	900	1050	1050	1050
Platform height min. h <sub>1</sub> , mm	255	335	340	360	360	360
Stroke h <sub>3</sub> , mm	525	505	560	690	690	690
Overall length l <sub>1</sub> , mm	990	1050	1320	1650	2350	1650
Overall width b <sub>1</sub> , mm	450	500	610	860	1000	860
Platform length l, mm	760	840	1.030	1350	2000	1350
Platform width b <sub>1</sub> , mm	450	500	610	840	1000	840
Tyre type**	VG	PUR	PUR	PA	PA	PA
Service brake	manual	manual	manual	manual	manual	manual
Number of strokes for max. lift	14	18	29	40	80	80
Weight (with battery and battery charger), kg	41	83	109	222	350	230

\*\*PA... Polyamide, PUR... Polyurethane, VG... Solid rubber

## Technical data model HF/SE

Model	HF 030-084 SE	HF 050-090 SE	HF 080-105 SE	HF 100-105 SE	HF 125-105 SE
Art.-No.	24603084	24605090	24608105	24610105	24612105
Capacity, kg	300	500	800	1000	1250
Platform height max. h <sub>2</sub> , mm	840	900	1050	1050	1050
Platform height min. h <sub>1</sub> , mm	335	340	360	360	360
Stroke h <sub>3</sub> , mm	505	560	690	690	690
Overall length l <sub>1</sub> , mm	1130	1330	1650	2350	1650
Overall width b <sub>1</sub> , mm	500	610	860	1000	860
Platform length l, mm	840	1030	1350	2000	1350
Platform width b <sub>1</sub> , mm	500	610	840	1000	840
Tyre type**	PUR	PUR	PA	PA	PA
Service brake	manual	manual	manual	manual	manual
Number of strokes for max. lift	electric	electric	electric	electric	electric
Weight (with battery and battery charger), kg	120	158	270	397	278

\*\* PA... Polyamide, PUR... Polyurethane

